

# CONVERSION TABLE WHEELS SIZES.

Size	Recommended rim width	Allowed rim width
7.50 R 15TT	6	6.00-6.50
8.25 R 15	6,5	6.00-7.00
9.5 R 17.5	6,75	6.00-6.75
11 R 22.5	7,5	7.50-8.25
12 R 22.5	8,25	8.25-9.00
12.00 R 20	8,5	7.50-9.00
12.00 R 24	8,5	8.5-9.0
13 R 22.5	9	9.00-9.75
14.00 R 20	10	9.0-10.00
205/65 R 17.5	6	6.00-6.75
205/75 R 17.5	6	5.25-6.75
215/75 R 17.5	6	6.00-6.75
225/75 R 17.5	6,75	6.00-6.75
235/75 R 17.5	6,75	6.75-7.50
245/70 R 17.5	7,5	6.75-7.50
245/70 R 19.5	6,75	6.75-7.50
255/70 R 22.5	7,5	6.75-8.25
265/55 R 19.5	8,25	8,25
265/70 R 17.5	7,5	6.75-8.25
265/70 R 19.5	7,5	7.50-8.25
275/70 R 22.5	7,5	7.50-8.25
285/70 R 19.5	8,25	7.50-9.00
295/55 R 22.5	9	9.00-9.75
295/60 R 22.5	9	9.00-9.75
295/80 R 22.5	8,25	8.25-9.00
305/70 R 19.5	9	8.25-9.00
305/70 R 22.5	8,25	8.25-9.00
315/45 R 22.5	9,75	9,75
315/60 R 22.5	9	9.00-9.75
315/70 R 22.5	9	9.00-9.75
315/80 R 22.5	9	9.00-9.75
325/95 R 24	9	8.5-10.00
355/50 R 22.5	11,75	11,75
365/85 R 20	10	10
375/45 R 22.5	11,75	11.75-12.25
375/50 R 22.5	11,75	11.75-12.25
375/90 R 22.5	11,75	10.5-11.75
385/55 R 22.5	11,75	11.75-12.25
385/65 R 22.5	11,75	11.75-12.25
425/65 R 22.5	13	12.25-14.00
435/50 R 19.5	14	14.00-15.00
445/65 R 22.5	13	13.00-14.00
445/75 R 22.5	13	13.00-14.00
455/40 R 22.5	15	15.00-16.00
455/45 R 22.5	15	14.00-15.00
495/45 R 22.5	17	16.00-17.00

